

EN305:2011 Construction Products Regulation DECLARATION OF PERFORMANCE

N. KF-015g

Unique identification code of the product-type: K-FIRE ACRYLIC

Intended use/es: Acrylic based sealant used to form linear gap

seals where gaps are present in wall and floor constructions and linear joint seals where wall

and floor constructions abut. See ETA 17/1047 21/12/2017

Manufacturer: L'Isolante K-Flex S.p.A.

Via Don G. Locatelli 35, 20877, Roncello, MB,

Italia

System/s of AVCP: 1

Harmonized standard: Not Available

Notified body: UL International (UK) Ltd

European Technical Approval: ETA 17/1047 21/12/2017

UL International (UK) Ltd issued European Technical Approval on the basis of ETAG 026-3

(08/2011).

Certificate of Conformity: 0843-CPR-0408

UL International (UK) Ltd performed third party tasks as set out in Annex V under System 1 and

issued Certificate of Conformity.

Declared performance/s:

Essential Characteristics	Performance
BWR 1 - Mechanical Resistance and stability	y
Mechanical Resistance and stability	NR
BWR 2 - Safety in case of fire	
Reaction to fire	D-s1, d1
Resistance to Fire	ETA 17/1047 21/12/2017, Annex A
BWR 3 - Hygiene, health and environment	
Air Permeability	NPD
Water Permeability	NPD
Release of dangerous substances	NPD
BWR 4 - Safety in use	
Mechanical Resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
BWR 5 - Protection against noise	•



via Don Locatelli, 35 20877 Roncello (MB) – Italy Tel.: +39 039.6824.1 (r.a.) fax: +39 039.6824560

pec.: isolantekflex@pec.it

www.kflex.com - info@isolante.com

Cap. Soc. € 56.700.000 i.v.
Codice fiscale 09470180150
Partita IVA IT 02423640966
Reg. Impr. Monza e Brianza n. MB 09470180150
R.E.A. 1868777



Airborne sound insulation	Rw(C;Ctr)= 62 (-1;-5) dB
BWR 6 - Energy economy and heat retention	
Thermal properties	NPD
Water vapor permeability	NPD
General Aspect relating to fitness for use	
Durability and Serviceability	Z2 - intended for uses in internal conditions with humidity lower than 85 % RH excluding temperatures below 0°C, without exposure to rain or UV.

NR Not Relevant NPD No Performance Determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 3052011, under the sole responsibility of the manufacturer identified above.

The Safety Data Sheet (SDS) of K-FIRE ACRYLIC is available on request..

Roncello (IT), 09/01/2018

Signed for and on behalf of the manufacturer by:



fax: +39 039.6824560 www.kflex.com - info@isolante.com pec.: isolantekflex@pec.it