

EN305:2011 Construction Products Regulation DECLARATION OF PERFORMANCE

N. KF-015p

Unique identification code of the product-type: K-FIRE ACRYLIC

Intended use/es: Sealant used to form a penetration seal around

metallic pipes, plastic pipes, composite pipes and electrical cables to reinstate the fire resistance performance of wall and floor constructions, where they have been provided with apertures for the penetration of services.

See ETA 17/1048 21/12/2017

Manufacturer: L'Isolante K-Flex S.p.A.

Via Don G. Locatelli 35, 20877, Roncello, MB,

Italia

System/s of AVCP: 1

Harmonized standard: Not Available

Notified body: UL International (UK) Ltd

European Technical Approval: ETA 17/1048 21/12/2017

UL International (UK) Ltd issued European Technical Approval on the basis of ETAG 026-2

(08/2011).

Certificate of Conformity: 0843-CPR-0408

UL International (UK) Ltd performed third party tasks as set out in Annex V under System 1 and

issued Certificate of Conformity.

Declared performance/s:

Essential Characteristics	Performance	
BWR 1 - Mechanical Resistance and stability		
Mechanical Resistance and stability	NR	
BWR 2 - Safety in case of fire		
Reaction to fire	D-s1, d1	
Resistance to Fire	ETA 17/1048 21/12/2017, Annex A	
BWR 3 - Hygiene, health and environment		
Air Permeability	NPD	
Water Permeability	NPD	
Release of dangerous substances	ETA 17/1048 21/12/2017, IA1, S/W3	
BWR 4 - Safety in use		
Mechanical Resistance and stability	NPD	
Resistance to impact/movement	NPD	



pec.: isolantekflex@pec.it

www.kflex.com - info@isolante.com



Adhesion	NPD
BWR 5 - Protection against noise	
Airborne sound insulation	NPD
BWR 6 - Energy economy and heat retention	
Thermal properties	NPD
Water vapor permeability	NPD
General Aspect relating to fitness for use	
Durability and Serviceability	Z2 - intended for uses in internal conditions with humidity lower than 85 % RH excluding temperatures below 0°C, without exposure to rain or UV.


NR Not Relevant NPD No Performance Determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 3052011, under the sole responsibility of the manufacturer identified above.

The Safety Data Sheet (SDS) of K-FIRE ACRYLIC is available on request..

Roncello (IT), 09/01/2018

Signed for and on behalf of the manufacturer by:



pec.: isolantekflex@pec.it

Cap. Soc. € 56.700.000 i.v.