

EN305:2011 Construction Products Regulation DECLARATION OF PERFORMANCE

N. KF-017g

Unique identification code of the product-type: K-FIRE COATING

Intended use/es: Ablative sealant coating designed to enhance,

seal and fire protect mineral fibres. Sprayed coating product that is site or factory applied to both faces of a stone wool, mineral fibre board

or site applied to one face of stone wool mineral fibre backer, to form a linear joint seal

system.

See ETA 17/1021 21/12/2017

Manufacturer: L'Isolante K-Flex S.p.A.

Via Don G. Locatelli 35, 20877, Roncello, MB,

Italia

System/s of AVCP: 1

Harmonized standard: Not Available

Notified body: UL International (UK) Ltd

European Technical Approval: ETA 17/1021 21/12/2017

UL International (UK) Ltd issued European Technical Approval on the basis of ETAG 026-2

(08/2011).

Certificate of Conformity: 0843-CPR-0407

UL International (UK) Ltd performed third party tasks as set out in Annex V under System 1 and

issued Certificate of Conformity.

Declared performance/s:

Essential Characteristics	Performance
BWR 1 - Mechanical Resistance and stability	1
Mechanical Resistance and stability	NR
BWR 2 - Safety in case of fire	
Reaction to fire	NPD
Resistance to Fire	ETA 17/1021 21/12/2017, Annex A
BWR 3 - Hygiene, health and environment	
Air Permeability	NPD
Water Permeability	NPD
Release of dangerous substances	BWR 4 - Safety in use
#Str23	
Mechanical Resistance and stability	NPD



Cap. Soc. € 56.700.000 i.v.



Resistance to impact/movement	NPD
Adhesion	NPD
BWR 5 - Protection against noise	
Airborne sound insulation	Rw(C;Ctr)= 55 (-1;-1) dB
BWR 6 - Energy economy and heat retent	ion
Thermal properties	NPD
Water vapor permeability	NPD
General Aspect relating to fitness for use	
Durability and Serviceability	Z2 - intended for uses in internal conditions with humidity lower than 85 % RH excluding temperatures below 0°C, without exposure to rain or UV.

NR Not Relevant NPD No Performance Determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 3052011, under the sole responsibility of the manufacturer identified above.

The Safety Data Sheet (SDS) of K-FIRE COATING is available on request..

Roncello (IT), 09/01/2018

Signed for and on behalf of the manufacturer by:





fax: +39 039.6824560 www.kflex.com - info@isolante.com pec.: isolantekflex@pec.it