

Safety Data Sheet

in accordance with Regulation (CE) n.1907/2006 (REACH)

K-FLEX K-FIRE SEALANT A PLUS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: K-FLEX K-FIRE SEALANT A PLUS

Trade code: isol010f

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Sealant for penetration through walls and floors for fire integrity and insulation.

Uses advised against: Not for consumer use

1.3. Details of the supplier of the safety data sheet

Company:

L' ISOLANTE K-FLEX UK Ltd

Unit 9 Coalville Business Park, Jackson St, Coalville, Leicestershire LE67 3NR, United

Kingdom Distributor:

L'Isolante K-Flex SpA

Via Leonardo da Vinci 36, 20877. Roncello, MB, Italy

Phone: +39 039 68 24.1

Competent person responsible for the information sheet:

Kflex-Reach@isolante.com
1.4. Emergency telephone number

L'Isolante K-Flex SpA Phone: +39 039 68 24.1

In case of accident, locate the nearest antipoison centres in the following link:

WHO http://apps.who.int/poisoncentres/

SECTION 2: Hazards identification

2.1. Classification of the mixture

EC regulation criteria 1272/2008 (CLP): Not Classified

Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:

Properties:

Not Classified

R Phrases:

Not Classified.

Adverse physicochemical, human health and environmental effects:

None

2.2. Label elements

Not required

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Does not contain asbestos, fibers, halogens or other classified materials.

K-FLEX K-FIRE SEALANT A PLUS Page n. 1 of 7





Safety Data Sheet

in accordance with Regulation (CE) n.1907/2006 (REACH)

K-FLEX K-FIRE SEALANT A PLUS

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:None

Components with Community Workplace exposure limit: None

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing and dispose off safely.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath). Do not use solvents or thinners. Seek medical attention if skin irritation accours and persists.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water for at least 15 minutes and seek medical advice.

In case of Ingestion:

Rinse out mouth with water. Drink plenty of water.

Do not under any circumstances induce vomiting. Obtain a medical examination immediately. In case of inhalation of dust produced from handling:

Remove casualty to fresh air and keep warm and at rest. Obtain a medical examination immediately

4.2. Most important symptoms and effects, both acute and delayed

There may be a mild irration at the site of contact.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None known to now.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale combustion gases. Fire can produce dense smoke containing hazardous products of combustion.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

K-FLEX K-FIRE SEALANT A PLUS Page n. 2 of 7





Safety Data Sheet

in accordance with Regulation (CE) n.1907/2006 (REACH)

K-FLEX K-FIRE SEALANT A PLUS

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil as a waste. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of entry into waterways, soil or drains as a waste, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes by hands contact, and inhalation.

Minimize and control dust when using.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Keep dry and protect from dampness and humidity.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

Strong oxidizers and acids.

Instructions as regards storage premises:

Store between +5 °C and +30 °C in a dry well-ventilated place away from sources of heat.

Protect from frost.

7.3. Specific end use(s)

Sealant for penetration through walls and floors for fire integrity and insulation.

The Manual Handling Regulation may apply to the handling of containers/packeges of this product In order to calculate the weight of any pack size, multiply the volume in litres by specific gravity value given in Section 9.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

None

DNEL Exposure Limit Values

None

PNEC Exposure Limit Values

None

LTEL Exposure Limit Values

None

8.2. Exposure controls

Eye protection:

Where excessive dust may result during the handling, wear approved mask.

Protection for skin:

Full protection suit.

K-FLEX K-FIRE SEALANT A PLUS Page n. 3 of 7



Unit 9, Coalville Business Park, Jackson Street, Coalville, LE67 3NR England Tel.: +0044 1530 834888

fax: +0044 1530 834500 www.kflex.com - info@isolante.com



Safety Data Sheet

in accordance with Regulation (CE) n.1907/2006 (REACH)

K-FLEX K-FIRE SEALANT A PLUS

Protection for hands:

Gloves with long cuffs.

For more detailed instructions, taking into account the user manual provided by the glove.

Respiratory protection:

The use of a dust mask or euivalent to EN 149 Category FFP2S, and the provision of dust extraction/ ventilation where dust is produced is reccommended. in case of insufficient ventilation of nuisance odors, wear appropriate respiratory equipment.

Combination filtering device (DIN EN 141).

Environmental exposure controls:

Exposure limit values have been established by many authorities. Check on limit values that apply in your local situation.

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

Local exhaust and general ventilation must be adequate to meet exposure standards. appropriate engineering controls.

According to:

Directive 2004/37/EC on the protection of workers from risk related to exposure carcinogens or mutagens at work.

Directive 98/24/EC-risk related to chemical agents at work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour: Viscous paste, white

Odour: None

Odour threshold: Not determined

pH: 7-9

Melting point / freezing point: Non applicable Initial boiling point and boiling range: Non applicable Solid/gas flammability: Not combustible Upper/lower flammability or explosive limits: Not available Vapour density: Not relevant Flash point: Above 100°C Evaporation rate: Not available Vapour pressure: Not applicable

Density: 1.62-1.66 Kg/m³ at 20 ℃

Solubility in water: Miscible

Solubility in oil:

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Not available

Explosive properties:

Oxidizing properties:

Not determined

Not available

Not available

Not available

9.2. Other information

Miscibility: With Water
Fat Solubility: Not available
Conductivity: Not available
Substance Groups relevant properties: Not Relevant

K-FLEX K-FIRE SEALANT A PLUS Page n. 4 of 7





Safety Data Sheet

in accordance with Regulation (CE) n.1907/2006 (REACH)

K-FLEX K-FIRE SEALANT A PLUS

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended transport of storage conditions

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reaction may occour with strong oxidizing agent. Stable product which does not cause any dangerous reaction with other substances.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Strong mineral acids (nitric acid, hydrochloric acid, sulfuric acid, hydrofluoric acid),

Avoid contact with strong oxidants.

Product in water becomes mildly alkaline. Contact with strong acide should be avoided.

10.6. Hazardous decomposition products

In combustion emits toxic fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

Not tested on this product. All ingredients are listed in EINEC8 and are not considered hazardous in the concetrations in which they are present.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- i) aspiration hazard.

Repeated or prolunged contac may lead to the removal of natural fats from the skin, resulting in non-allergic dermatitis. Splashes in the eye may cause irritation and reversible local damage.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. No toxic effect are described in Ecotoxicological study available

12.2. Persistence and degradability

Biodegradable

12.3. Bioaccumulative potential

No data available on the product and no biocaccumulation potential

12.4. Mobility in soil

No data available on product

K-FLEX K-FIRE SEALANT A PLUS Page n. 5 of 7



Unit 9, Coalville Business Park, Jackson Street, Coalville, LE67 3NR England Tel.: +0044 1530 834888 fax: +0044 1530 834500

www.kflex.com - info@isolante.com



Safety Data Sheet

in accordance with Regulation (CE) n.1907/2006 (REACH)

K-FLEX K-FIRE SEALANT A PLUS

12.5. Results of PBT and vPvB assessment

No data available on product

12.6. Other adverse effects

None known to now

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Wastes, should be disposed at a site suitable for building products and in accordance with local regulation. Waste disposal in landfill (solid waste).

For this product inceneration is not recommended.

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

Not classified as dangerous in the meaning of transport regulations.

14.3. Transport hazard class(es)

Not classified as dangerous in the meaning of transport regulations.

14.4. Packing group

Not classified as dangerous in the meaning of transport regulations.

14.5. Environmental hazards

Not classified as dangerous in the meaning of transport regulations.

14.6. Special precautions for user

Not classified as dangerous in the meaning of transport regulations.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not classified as dangerous in the meaning of transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)

Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Dir. 2006/8/EC

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP)

Regulation (EU) n. 453/2010 (Annex I)

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Where applicable, refer to the following regulatory provisions:

Directive 76/464/EEC: Water pollution by discharges of certain dangerous substances

Directive 80/68/EEC: on the protection of groundwater against pollution caused by certain dangerous substances

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments

5.2. Chemical safety assessment

NΙΛ

K-FLEX K-FIRE SEALANT A PLUS Page n. 6 of 7





Safety Data Sheet

in accordance with Regulation (CE) n.1907/2006 (REACH)

K-FLEX K-FIRE SEALANT A PLUS

SECTION 16: Other information

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECHA database GESTIS Database ACGIH Publication of 2012

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods. LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

PNEC: Predicted No Effect Concentration. LGK Storage classes (Germany only)

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day.

(ACGIH Standard).

WGK: German Water Hazard Class.

