

CE EN305:2011 Construction Products Regulation **DECLARATION OF PERFORMANCE**

No. KF-EN-010g

Unique identification code of the product-type:	K-FIRE SEALANT A PLUS
Intended use/es:	Acrylic based sealant used to form linear gap seals where gaps are present in wall and floor constructions and linear joint seals where wall and floor constructions abut. See ETA 15/0795
Manufacturer:	L'Isolante K-Flex UK Ltd. Unit 9, Coalville Business Park, Jackson Street, Coalville, LE67 3NR, England
System/s of AVCP:	1
Harmonized standard:	Not Available
Notified body:	UL International (UK) Ltd
European Technical Approval	ETA-15/0795 UL International (UK) Ltd issued European Technical Approval on the basis of ETAG 026-3 (2011).
Certificate of Conformity	0843–CPR–0284 UL International (UK) Ltd performed third party tasks as set out in Annex V under System 1 and issued Certificate of Conformity.

Declared performance/s:

Essential Characteristics	Performance
BWR 1	Mechanical Resistance and stability
Mechanical Resistance and stability	Not Relevant
BWR 2	Safety in case of fire
Reaction to fire	F
Resistance to Fire	ETA 15/0795, Annex A
BWR 3	Hygiene, health and environment
Air Permeability	NPD
Water Permeability	NPD
Release of dangerous substances	IA1, S/W3
BWR 4	Safety in use



L'ISOLANTE K-FLEX S.p.A.

via Leonardo Da Vinci, 36 20877 Roncello (MB) - Italy Tel.: +39 039.6824.1 (r.a.) fax: +39 039.6824560 www.kflex.com - info@isolante.com pec.: isolantekflex@pec.it



Mechanical Resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
BWR 5	Protection against noise
Airborne sound insulation	NPD
BWR 6	Energy economy and heat retention
Thermal properties	NPD
Water vapor permeability	NPD
	General Aspect relating to fitness for use
Durability and Serviceability	Z1 Intended for use at internal conditions with high or other humidity classes, excluding temperatures below 0°C.

NPD = No Performance Determined.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305:2011, under the sole responsibility of the manufacturer identified above.

Coalville, 25/03/2016

Signed for and on behalf of the manufacturer by:

Jundes fill

Amedeo Spinelli President

🔀 L'ISOLANTE K-FLEX S.p.A.

via Leonardo Da Vinci, 36 20877 Roncello (MB) – Italy Tel.: +39 039.6824.1 (r.a.) fax: +39 039.6824560 www.kflex.com - info@isolante.com pec.: isolantekflex@pec.it